

Pacer 3 inch BSP(F) poly pump Yanmar diesel Electric start (Buna-N diesel seals) 870 lpm 37 m head



Code: 10.1156AB

Pacer 3 inch BSP(F) poly pump
Yanmar L48N 4.7 hp diesel engine
Electric and recoil start
Battery and leads not included
Type 706 impeller (5 vane)
Buna-N seals for oil and diesel

Dimensions:

360 x 384 x 417 mm (L x W x H)

features :

Pacer 2 inch 706 S-series poly pump
2 inch BSP(F) ports
Glass-reinforced black polyester
Lightweight
Corrosion resistant
5 vane type 706 impeller
Built-in check valve
Self-priming to 7.6 m (25 ft)
757 lpm (200 gpm)
40 m (131 ft) head
4 bar (58 psi)
Yanmar diesel engine
Model L48N

Performance:

3.1 kW (4.2 hp) @ 3600 rpm continuous
3.5 kW (4.7 hp) @ 3600 rpm rated
2.8 kW (3.8 hp) @ 3000 rpm continuous
3.1 kW (4.2 hp) @ 3000 rpm rated

Capacities:

2.4 litre fuel tank
0.8 litre crankcase oil capacity
Recommended engine oil:
SAE 10W30 diesel engine oil

Fuel consumption:

0.78 litres per hour @ 3000 rpm (75% load)
Aprox 3 hours run time per 2.4 litre fuel tank
Aprox 57 hours run time per 45 litre fuel tank

